


hydraulic connection G 1/2"



optional limit switch:  
lining wear

optional limit switch:  
brake open / close

Mounting Studs			
n	quantity		14
	size, grade		M30, 10.9
M <sub>A</sub>	fastening torque	Nm	2000 at μ=0,14
Linings			
	material		sinter
	friction coefficient *		0,4

\*average friction coefficient with standard material combination and a circumferential speed up to 15 m/s

SHI-Type		281 FC	282 FC
<b>Clamping Force F<sub>A</sub></b>			
F <sub>A</sub>	with airgap c = 1 mm	kN	425
F <sub>A</sub>	with airgap c = 1,5 mm	kN	395
<b>Torque Calculation</b>			
M <sub>Br</sub>	braking torque Nm	2 x F <sub>A</sub> x μ x (d/2-112.5)	
<b>Hydraulic</b>			
P <sub>L</sub>	release pressure	bar	135
P <sub>max</sub>	max. pressure	bar	175
V <sub>max</sub>	volume at c= 1,5 mm	ltr	0,09
<b>Brake Discs</b>			
b	disc thickness	mm	30 ≤ b ≤ 40
d	disc-Ø	mm	1600 ≤ d ≤ 5000
d <sub>1</sub>	max. hub- / drum-Ø	mm	d - 545
<b>Dimensions</b>			
L x W x H = 535 x (675+b) x 1030 mm			
max. weight: 965 kg			

When ordering please advise: right hand version, as shown;  
left hand version, mirror inverted!